

FEATURES

- * 1.22 inch (31.0 mm) MATRIX HEIGHT.
- * LOW POWER REQUIREMENT.
- * SINGLE PLANE, WIDE VIEWING ANGLE.
- * SOLID STATE RELIABILITY.
- * 8 × 8 ARRAY WITH X-Y SELECT.
- * COMPATIBLE WITH USASCII AND EBCDIC CODES.
- * STACKABLE HORIZONTALLY.


DESCRIPTION

The LTP-12788BKY is a 1.22 inch (31.0 mm) matrix height 8 × 8 dot matrix display. The AlInGaP amber yellow LED chips, which are made from AlInGaP on a non-transparent GaAs substrate. The device has black face and transparent dots.

DEVICE


PART NO.	DESCRIPTION
AlInGaP AMBER YELLOW	ANODE ROW
LTP-12788BKY	CATHODE COLUMN

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm (0.01") unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



PIN CONNECTION

NO	CONNECTION	NO	CONNECTION
1	NO CONNECT	13	ANODE ROW 4
2	CATHODE COLUMN 5	14	CATHODE COLUMN 4
3	ANODE ROW 5	15	NO CONNECT
4	NO CONNECT	16	ANODE ROW 3
5	CATHODE COLUMN 6	17	CATHODE COLUMN 3
6	ANODE ROW 6	18	NO CONNECT
7	NO CONNECT	19	ANODE ROW 2
8	CATHODE COLUMN 7	20	CATHODE COLUMN 2
9	ANODE ROW. 7	21	NO CONNECT
10	NO CONNECT	22	ANODE ROW 1
11	CATHODE COLUMN 8	23	CATHODE COLUMN 1
12	ANODE ROW 8	24	NO CONNECT

ABSOLUTE MAXIMUM RATING AT Ta=25°C

PARAMETER	AllnGaP AMBER YELLOW	UNIT
Average Power Dissipation Per Dot	35	mW
Peak Forward Current Per Dot	60	mA
Average Forward Current Per Dot	13	mA
Derating Linear From 25°C Per Dot	0.17	mA/°C
Reverse Voltage Per Dot	5	V
Operating Temperature Range	-35°C to +85°C	
Storage Temperature Range	-35°C to +85°C	
Solder Temperature: max 260°C for max 3sec at 1.6mm[1/16inch] below seating plane.		

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I _v	13700	34000		μcd	I _p =32mA 1/16Duty
Peak Emission Wavelength	λ _p		595		nm	I _F =20mA
Spectral Line Half-Width	Δλ		15		nm	I _F =20mA
Dominant Wavelength	λ _d		592		nm	I _F =20mA
Forward Voltage any Dot	V _F		2.05	2.6	V	I _F =20mA
Reverse Current any Dot	I _R			100	μA	V _R =5V
Luminous Intensity Matching Ratio	I _v -m			2:1		I _p =32mA 1/16Duty

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)




Fig1. RELATIVE INTENSITY VS. WAVELENGTH




Fig2. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT




Fig3. FORWARD CURRENT VS. FORWARD VOLTAGE




Fig4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig5. MAX AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE




Fig6. MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)

NOTE: KY=AlInGaP AMBER YELLOW